



Non-rusting and highly flexible stainless steel protection conduit; robust; hooked metal profile

Applications

- cable protection: cable protection conduit, cable protection tube, cable protection hose, electric installation, switch cabinets, switch cabinet installation, cable harnessing/ cable assembly

Properties

- IP 40 to EN/ IEC 60529
- highly flexible

- extremely heat resistant
- increased resistance to tear, pressure and impact
- conforms to RoHS guideline

Temperature range

- up to 1.100 °F

Design

- Metal hose
- profiled metal strip, stainless steel (INOX)
- hooked profile

Delivery variants

- further diameters and lengths available on request

Nominal width connecting part (in)	I.D. (mm)	outer Ø (in)	Bending radius (middle of hose) (in)	Weight (lb/ft)	PU (ft)	Order No.
0.236	0.157	0.236	0.591	0.034	164.050	108-3006-9050
0.276	0.197	0.276	0.669	0.034	164.050	108-3007-9050
0.315	0.236	0.315	0.787	0.040	164.050	108-3008-9050
0.394	0.315	0.394	0.984	0.047	164.050	108-3010-9050
0.551	0.433	0.551	1.339	0.081	164.050	108-3014-9050
0.669	0.551	0.669	1.575	0.101	164.050	108-3017-9050
0.748	0.630	0.748	1.772	0.114	164.050	108-3019-9050
0.827	0.709	0.827	1.969	0.128	164.050	108-3021-9050
1.063	0.906	1.063	2.638	0.215	164.050	108-3027-9050
1.417	1.220	1.417	3.543	0.336	82.025	108-3036-9025
1.772	1.575	1.772	4.331	0.470	82.025	108-3045-9025

Accessories



GM 164



AU 159



GK 169