



Metal counter nut

### Applications

- Cable protection: accessory for cable protection screw connection for assembling of fitting protection hose, electric installation, switch cabinets, switch cabinet installation, cable harnessing/ cable assembly

### Properties

- thread reference: M (metric) to EN 60423, P (PG) to DIN 40430
- conforms to RoHS guideline

### Design

- accessories
- nickel-plated brass

### Delivery variants

- further diameters available on request

Outer thread metric	Thread	Thickness	Wrench Size across Flats SW	Weight	PU	Order No.
M EN 60423	PG DIN 40430	(mm)	(mm)	(kg/100pcs)	(Pcs)	
M 12 x 1,5	-	3	15	0,2	50	164-8012-9050
M 16 x 1,5	-	3	20	0,4	50	164-8016-9050
M 20 x 1,5	-	3,5	24	0,6	50	164-8020-9050
M 25 x 1,5	-	3,5	30	1	25	164-8025-9025
M 32 x 1,5	-	4,5	35	1,15	20	164-8032-9020
M 40 x 1,5	-	4,5	45	1,9	10	164-8040-9010
M 50 x 1,5	-	5,5	55	3,1	10	164-8050-9010
M 63 x 1,5	-	6	70	5,8	5	164-8063-9005
-	PG 7	2,9	15	0,2	50	164-9007-9050
-	PG 9	2,9	18	0,3	50	164-9009-9050
-	PG 11	3,1	21	0,3	50	164-9011-9050
-	PG 13,5	3,1	23	0,4	50	164-9013-9050
-	PG 16	3,1	26	0,5	50	164-9016-9050
-	PG 21	3,6	32	0,8	20	164-9021-9020
-	PG 29	4,1	41	1,3	20	164-9029-9020
-	PG 36	5,1	51	2	10	164-9036-9010
-	PG 42	5,1	60	2,3	5	164-9042-9005
-	PG 48	5,6	64	3,2	5	164-9048-9005

## Accessories



AU 159

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).