


CONNECT 206



Connectors for connecting or attaching metal hoses

Properties

- conforms to RoHS guideline

- Quick-release coupling 206**: quick-release coupling with several clamp clips, option of coupling with clamp clips or flange with flat face, extension at one end for attaching the metal hose
- REACH according to --> Technology / Technical Information / REACH

Design

- Stainless Steel (INOX)

Delivery variants

- further diameters available on request

No. clamp clips	Suitable for hose I.D. (in)	Order No.
Assembly; (please select the hose separately); riveting		
-	-	206-0000-2905
Quick-release coupling 206 Coupling with clamp clips stainless steel (INOX)		
2	100	206-0100-2015
2	125	206-0125-2015
2	150	206-0150-2015
3	200	206-0200-2015
3	250	206-0250-2015
3	300	206-0300-2015
Quick-release coupling 206 flange stainless steel (INOX)		
2	100	206-0100-2016
2	125	206-0125-2016
2	150	206-0150-2016
3	200	206-0200-2016
3	250	206-0250-2016
3	300	206-0300-2016

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.