

CLAMP 210 BRIDGE CLAMP



Clamp with plastic bridge for attaching externally corrugated spiral hoses

Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable

Design

- multi-piece
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Design

- Bridge: PA6
- Quality: W1; Clamp strip + screw + body: galvanised steel

Delivery variants

- Comes as a 10 pack loosely sealed in a bag
- silver

Suitable for Hose I.D.	Band Width	PU	Order No.
(mm)	(mm)	(Pcs)	
25-31	9	10	210-0025-0000
32-39	9	10	210-0032-0000
40-49	9	10	210-0040-0000
50-59	9	10	210-0050-0000
60-69	9	10	210-0060-0000
70-79	9	10	210-0070-0000
80-89	9	10	210-0080-0000
90-99	9	10	210-0090-0000
100-109	9	10	210-0100-0000
110-119	9	10	210-0110-0000
120-129	9	10	210-0120-0000
130-139	9	10	210-0130-0000
140-149	9	10	210-0140-0000
150-159	9	10	210-0150-0000
160-169	9	10	210-0160-0000
170-179	9	10	210-0170-0000
180-189	9	10	210-0180-0000
190-199	9	10	210-0190-0000
200-209	9	10	210-0200-0000

Accessories



CONNECT 228



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.