

# CLAMP 211



T-bolt clamp for attaching heavy-duty hoses with a smooth outer wall

## Properties

- easily and quickly fitted
- re-usable

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Design

- Quality: W1; Clamp strip + screw: galvanised steel
- Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; Screw: galvanised steel
- Quality: W4; Clamp strip + screw: stainless steel 1.4301 = AISI 304

suitable for hose Ø-outside (mm)	Clamping Range (mm)	Band Width (mm)	PU (Pcs)	Order No.
<b>W1</b>				
17-19	17-19	18	1	211-0021-0000
20-22	20-22	18	1	211-0023-0000
23-25	23-25	18	1	211-0025-0000
26-28	26-28	18	1	211-0029-0000
29-31	29-31	18	1	211-0031-0000
31-34	31-34	18	1	211-0034-0000
36-39	36-39	18	1	211-0040-0000
40-43	40-43	18	1	211-0043-0000
44-47	44-47	20	1	211-0047-0000
48-51	48-51	20	1	211-0051-0000
52-55	52-55	20	1	211-0055-0000
56-59	56-59	20	1	211-0059-0000
60-63	60-63	20	1	211-0063-0000
64-67	64-67	20	1	211-0068-0000
68-73	68-73	25	1	211-0073-0000
74-79	74-79	25	1	211-0079-0000
80-85	80-85	25	1	211-0085-0000
86-91	86-91	25	1	211-0091-0000
92-97	92-97	25	1	211-0097-0000
98-103	98-103	25	1	211-0104-0000
104-112	104-112	25	1	211-0112-0000
113-121	113-121	25	1	211-0121-0000
122-130	122-130	25	1	211-0130-0000
131-139	131-139	30	1	211-0140-0000
140-148	140-148	30	1	211-0150-0000
149-161	149-161	30	1	211-0162-0000
162-174	162-174	30	1	211-0174-0000
175-187	175-187	30	1	211-0187-0000
188-200	188-200	30	1	211-0200-0000
201-213	201-213	30	1	211-0213-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).

# CLAMP 211

suitable for hose Ø-outside (mm)	Clamping Range (mm)	Band Width (mm)	PU (Pcs)	Order No.
214-226	214-226	30	1	211-0226-0000
227-239	227-239	30	1	211-0239-0000
240-252	240-252	30	1	211-0252-0000

W2				
17-19	17-19	18	1	211-0021-9200
20-22	20-22	18	1	211-0023-9200
23-25	23-25	18	1	211-0025-9200
26-28	26-28	18	1	211-0029-9200
29-31	29-31	18	1	211-0031-9200
31-34	31-34	18	1	211-0034-9200
36-39	36-39	18	1	211-0040-9200
40-43	40-43	18	1	211-0043-9200
44-47	44-47	20	1	211-0047-9200
48-51	48-51	20	1	211-0051-9200
52-55	52-55	20	1	211-0055-9200
56-59	56-59	20	1	211-0059-9200
60-63	60-63	20	1	211-0063-9200
64-67	64-67	20	1	211-0068-9200
68-73	68-73	25	1	211-0073-9200
74-79	74-79	25	1	211-0079-9200
80-85	80-85	25	1	211-0085-9200
86-91	86-91	25	1	211-0091-9200
92-97	92-97	25	1	211-0097-9200
98-103	98-103	25	1	211-0104-9200
104-112	104-112	25	1	211-0112-9200
113-121	113-121	25	1	211-0121-9200
122-130	122-130	25	1	211-0130-9200
131-139	131-139	30	1	211-0140-9200
140-148	140-148	30	1	211-0150-9200
149-161	149-161	30	1	211-0162-9200
162-174	162-174	30	1	211-0174-9200
175-187	175-187	30	1	211-0187-9200
188-200	188-200	30	1	211-0200-9200
201-213	201-213	30	1	211-0213-9200
214-226	214-226	30	1	211-0226-9200
227-239	227-239	30	1	211-0239-9200
240-252	240-252	30	1	211-0252-9200

W4				
26-28	26-28	18	1	211-0029-9230
29-31	29-31	18	1	211-0031-9230
31-34	31-34	18	1	211-0034-9230
36-39	36-39	18	1	211-0040-9230
44-47	44-47	20	1	211-0047-9230
48-51	48-51	20	1	211-0051-9230
52-55	52-55	20	1	211-0055-9230
56-59	56-59	20	1	211-0059-9230
60-63	60-63	20	1	211-0063-9230
64-67	64-67	20	1	211-0068-9230
68-73	68-73	25	1	211-0073-9230
74-79	74-79	25	1	211-0079-9230
80-85	80-85	25	1	211-0085-9230

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).

## CLAMP 211

suitable for hose Ø-outside (mm)	Clamping Range (mm)	Band Width (mm)	PU (Pcs)	Order No.
86-91	86-91	25	1	211-0091-9230
92-97	92-97	25	1	211-0097-9230
98-103	98-103	25	1	211-0104-9230
104-112	104-112	25	1	211-0112-9230
113-121	113-121	25	1	211-0121-9230
122-130	122-130	25	1	211-0130-9230
131-139	131-139	30	1	211-0140-9230
140-148	140-148	30	1	211-0150-9230
149-161	149-161	30	1	211-0162-9230
162-174	162-174	30	1	211-0174-9230
175-187	175-187	30	1	211-0187-9230
188-200	188-200	30	1	211-0200-9230
201-213	201-213	30	1	211-0213-9230
214-226	214-226	30	1	211-0226-9230
227-239	227-239	30	1	211-0239-9230
240-252	240-252	30	1	211-0252-9230

## Accessories



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).