



Soft sleeve for SuperFlex hoses

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)

- good resistance to alkalis and acids
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -20°C to 70°C
- short time to 80°C

Design

- wall: high grade soft PVC

Delivery variants

- further diameters available on request
- black (standard)

| Rec. Adapter Ø | Rec. Adapter length | Threading depth Hose | Total Length | Weight | Suitable for Hose I.D. | Order No. |
|--|---------------------|----------------------|--------------|----------|------------------------|---------------|
| (mm) | (mm) | (mm) | (mm) | (kg/pcs) | (mm) | |
| Suitable for hose 372-....-0000 | | | | | | |
| 25 | 50 | 45 | 100 | 0,050 | 25 | 226-0025-0000 |
| 32 | 50 | 45 | 100 | 0,060 | 32 | 226-0032-0000 |
| 38 | 50 | 45 | 100 | 0,070 | 38 | 226-0038-0000 |
| 41 | 50 | 45 | 100 | 0,070 | 41 | 226-0041-0000 |
| 44 | 50 | 45 | 100 | 0,080 | 44 | 226-0044-0000 |
| 51 | 50 | 45 | 100 | 0,090 | 51 | 226-0051-0000 |
| 63 | 50 | 45 | 100 | 0,130 | 63 | 226-0063-0000 |
| 70 | 45 | 45 | 100 | 0,150 | 70 | 226-0070-0000 |
| 76 | 45 | 45 | 100 | 0,170 | 76 | 226-0076-0000 |

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.