



Soft sleeve to slide onto connectors or push into pipes, foodgrade

Applications

- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses
- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)

- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- version 241: material food grade according to EU 10/2011, FDA 21 CFR 177.1680 and CFR 177.2600
- Food grade wall, complies with: EU-Directive 10/2011, EC 1935/2004 and EU 2015/174
- odourless and tasteless
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C
- short time to 125 °C

Design

- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- special colours: full coloured

Rec. Adapter Ø (mm)	Rec. Adapter length (mm)	Threading depth Hose (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
38	44	40	85	0,085	38	240-0038-0010
40	44	40	85	0,084	40	240-0040-0010
50	49	41	90	0,089	50	240-0050-0010
60	49	41	90	0,120	60	240-0060-0010
70	52	44	100	0,146	70	240-0070-0010
32	44	40	85	0,070	32	241-0032-8600
75	60	47	107	0,200	75	241-0075-8600
80	60	52	112	0,250	80	241-0080-8600
100	65	57	122	0,310	100	241-0100-8600
125	75	62	137	0,480	125	241-0125-8600
150	85	70	155	0,680	150	241-0150-8600
200	100	80	180	1,100	200	241-0200-8600
250	105	90	195	1,500	250	241-0250-8600
300	115	100	215	2,260	300	241-0300-8600
pre-fitted						
32	44	40	85	0,070	32	241-0032-8550
40	44	40	85	0,080	40	241-0040-8550
50	49	41	90	0,080	50	241-0050-8550
60	49	41	90	0,120	60	241-0060-8550
80	60	52	112	0,250	80	241-0080-8550
100	65	57	122	0,310	100	241-0100-8550

Threaded; Suitable for Hose 356

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.

CONNECT 240 + 241 FOOD



Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
40	44	40	85	0,080	40	241-0040-8601
60	49	41	90	0,120	60	241-0060-8601
75	60	47	107	0,200	75	241-0075-8601
80	60	52	112	0,250	80	241-0080-8601

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.