



Soft sleeve to slide onto connectors or push into pipes, electrically conductive

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- electrically conductive wall: electrical and surface resistance $<10^3 \Omega$ (according to NFPA 652 $<10^6 \Omega$)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40°C to 90°C
- short time to 125°C

Design

- Wall of EC version electrically conductive $<10^3$: electrically conductive Premium Ester-Polyurethane (Pre-PUR[®])

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured

Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
38	44	40	85	0,094	38	240-0038-1003
40	44	40	85	0,087	40	240-0040-1003
50	49	41	90	0,103	50	240-0050-1003
60	49	41	90	0,133	60	240-0060-1003
70	52	44	96	0,163	70	240-0070-1003