



Soft sleeve to slide onto connectors or push into pipes, electrically conductive

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- electrically conductive wall: electrical and surface resistance $<10^3 \Omega$ (according to NFPA 652 $<10^6 \Omega$)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -40 °F to 195 °F
- short time to 255 °F

Design

- Wall of EC version electrically conductive $<10^3$: electrically conductive Premium Ester-Polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colors: full colored

Rec. adapter Ø (in)	Rec. adapter length (in)	Threading depth hose (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
1.496	1.732	1.575	3.346	0.207	38	240-0038-1003
1.575	1.732	1.575	3.346	0.192	40	240-0040-1003
1.969	1.929	1.614	3.543	0.227	50	240-0050-1003
2.362	1.929	1.614	3.543	0.293	60	240-0060-1003
2.756	2.047	1.732	3.780	0.359	70	240-0070-1003