


CONNECT 270-271



Metal hose connector / reducer

Properties

- easily and quickly fitted
- re-usable (threaded version)
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

Temperature range

- 390 °F

Design

- galvanised sheet metal

Delivery variants

- further diameters available on request
- stainless steel (INOX)

Suitable for Hose Ø-D1 (in)	Suitable for Hose Ø-D2 (in)	Adapter length L1 (in)	Adapter length L2 (in)	Total Length (in)	Wall thickness (in)	Weight (lb/pcs)	Order No.
Hose connector							
1.969	1.969	1.575	1.575	0.000	0.024	0.441	270-0050-0000
2.362	2.362	1.575	1.575	0.000	0.024	0.441	270-0060-0000
2.756	2.756	1.575	1.575	0.000	0.024	0.441	270-0070-0000
2.953	2.953	1.575	1.575	0.000	0.024	0.441	270-0075-0000
3.150	3.150	1.575	1.575	0.000	0.024	0.441	270-0080-0000
3.543	3.543	1.575	1.575	0.000	0.024	0.441	270-0090-0000
3.937	3.937	1.575	1.575	0.000	0.024	0.441	270-0100-0000
4.331	4.331	1.575	1.575	0.000	0.024	0.662	270-0110-0000
4.724	4.724	1.575	1.575	0.000	0.024	0.662	270-0120-0000
4.921	4.921	1.575	1.575	0.000	0.024	0.662	270-0125-0000
5.118	5.118	1.575	1.575	0.000	0.024	0.662	270-0130-0000
5.512	5.512	1.575	1.575	0.000	0.024	0.882	270-0140-0000
5.906	5.906	1.575	1.575	0.000	0.024	1.103	270-0150-0000
6.299	6.299	1.575	1.575	0.000	0.024	1.103	270-0160-0000
6.693	6.693	1.575	1.575	0.000	0.024	1.103	270-0170-0000
6.890	6.890	1.575	1.575	0.000	0.024	1.323	270-0175-0000
7.087	7.087	1.575	1.575	0.000	0.024	1.323	270-0180-0000
7.874	7.874	1.575	1.575	0.000	0.024	1.323	270-0200-0000
8.465	8.465	1.575	1.575	0.000	0.024	1.544	270-0215-0000
8.858	8.858	1.575	1.575	0.000	0.024	1.544	270-0225-0000
9.843	9.843	2.362	2.362	0.000	0.024	1.764	270-0250-0000
10.827	10.827	2.362	2.362	0.000	0.024	1.985	270-0275-0000
11.811	11.811	2.362	2.362	0.000	0.028	2.205	270-0300-0000
12.402	12.402	2.362	2.362	0.000	0.028	2.426	270-0315-0000
12.795	12.795	2.362	2.362	0.000	0.028	2.646	270-0325-0000
13.780	13.780	2.362	2.362	0.000	0.028	2.867	270-0350-0000
14.764	14.764	3.150	3.150	0.000	0.028	3.308	270-0375-0000
15.748	15.748	3.150	3.150	0.000	0.028	3.528	270-0400-0000
17.717	17.717	3.150	3.150	0.000	0.028	4.631	270-0450-0000
19.685	19.685	3.150	3.150	0.000	0.028	5.072	270-0500-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

CONNECT 270-271

Suitable for Hose Ø-D1 (in)	Suitable for Hose Ø-D2 (in)	Adapter length L1 (in)	Adapter length L2 (in)	Total Length (in)	Wall thickness (in)	Weight (lb/pcs)	Order No.
Hose reduction							
2.953	1.969	1.575	1.575	0.000	0.024	0.441	271-0075-0000
3.150	2.756	1.575	1.575	0.000	0.024	0.441	271-0080-0000
3.150	1.969	1.575	1.575	0.000	0.024	0.441	271-0080-2655
3.937	3.150	1.575	1.575	0.000	0.024	0.441	271-0100-0000
3.937	2.756	1.575	1.575	0.000	0.024	0.441	271-0100-2660
4.921	3.937	1.575	1.575	0.000	0.024	0.662	271-0125-0000
4.921	3.150	1.575	1.575	0.000	0.024	0.662	271-0125-2665
5.906	3.937	1.575	1.575	0.000	0.024	0.662	271-0150-0000
5.906	3.150	1.575	1.575	0.000	0.024	0.882	271-0150-2670
5.906	4.921	1.575	1.575	0.000	0.024	0.662	271-0150-2671
7.874	5.906	1.575	1.575	0.000	0.024	1.103	271-0200-0000
7.874	3.937	1.575	1.575	0.000	0.024	1.323	271-0200-2675
7.874	4.921	1.575	1.575	0.000	0.024	1.323	271-0200-2676
9.843	7.874	2.362	1.575	0.000	0.024	1.764	271-0250-0000
9.843	4.921	2.362	1.575	0.000	0.024	2.205	271-0250-2680
9.843	5.906	2.362	1.575	0.000	0.024	1.985	271-0250-2681
11.811	7.874	2.362	1.575	0.000	0.028	2.646	271-0300-0000
11.811	5.906	2.362	1.575	0.000	0.028	2.867	271-0300-2685
11.811	9.843	2.362	1.575	0.000	0.028	2.867	271-0300-2687

Accessories




CLAMP 212



CLAMP 211



CLAMP 217



CONNECT 228

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.