



Air pressure/ water hose

Aplikace

- for medium-duty applications in industry, workshops and on construction sites
- Suitable for the transport of water, air and compressed air containing oil

Vlastnosti

- particularly robust, thick-walled and flexible
- resistant to oil mist

- construction cover resistant to ageing, ozone, UV and weathering
- maximum operating pressure: air 10 bar, water 16 bar
- burst pressure 54 bar
- according to the norms EN ISO 1307:2008 and DIN 20018

Teplotní rozsah

- -30 °C až 50 °C

Konstrukce

- Inner tube made of thermoplastic elastomer
- Outer layer made of thermoplastic elastomer
- hladká uvnitř i vně
- Polyester plies

Varianty k dodání

- černá

Vnitřní průměr	Vnější průměr	Hrúbost stěny	Poloměr ohybu	Hmotnost	Rozměry skladem	Číslo
(in / mm)	(mm)	(mm)	(mm)	(kg/m)	(m)	objednávky
1/4 / 6	13.00	3.50	50.00	0.14	40 100	3201-006-000
- / 8	15.00	3.50	65.00	0.18	40 100	3201-008-000
- / 9	16.00	3.50	70.00	0.19	40	3201-009-000
3/8 / 10	19.00	4.50	70.00	0.28	40 100	3201-010-000
1/2 / 13	23.00	5.00	80.00	0.43	40 50	3201-013-000
5/8 / 15	27.00	6.00	100.00	0.54	40	3201-015-000
3/4 / 19	31.00	6.00	150.00	0.61	20 40 50	3201-019-031
1 / 25	39.00	7.00	185.00	0.88	40	3201-025-000

Při přetlaku a podtlaku doporučujeme dodržet hranici provozní hodnoty. Bližší informace o vyšším zatížení jsou dostupné na vyžádání. Poloměr ohybu je měřen podle vnitřního zahnutí hadice. Právo učinit technické změny je vyhrazeno. Všechny hodnoty jsou stanoveny při teplotě 20 °C a jsou jen přibližné. Další technické údaje jsou dostupné na www.norres.com/cz/technologie/.