



Vacuum truck hose, heavy and reinforced, very flexible

### Applications

- suction excavator
- municipal vehicle: sweeper, sweeping machine

### Properties

- heavy duty and reinforced
- highly abrasion resistant
- microbe resistant
- good resistance to oil, gasoline and chemicals

- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- -40 °C to 90 °C
- short time to 125 °C

### Design

- AIRDUC® profile hose

- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 2,5 mm approx.
- reinforcement of the primary abrasion areas

### Delivery variants

- further diameters and lengths available on request
- orange (standard)
- special colours: transparent, full coloured
- customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
8 / 200-203	213.00	0,600	0,120	316.00	5.13	-	5	355-0200-5202

## Accessories



CLAMP 211



CONNECT 240 + 241 AS



CONNECT 270-271