

Metal hose, suction hose (up to +400 °C)

Applications

- hose/ ducting for high volume of abrasive powder, bulk material, granulate and for gases
- explosion hazard area
- extraction unit, dedusting system, filter system, oil mist extraction
- wood dust extraction, wood chips: furniture production, saw mill
- paper mill, paper and pulp industry, packaging machine: edge strip suctioning system/ edge trim exhaust systems
- high temperature extraction: oven, foundry, furnace, smelting, ceramics industry, glass industry, steel plant, aluminium mill

Properties

- abrasion-resistant
- very good heat resistance
- flame-retardant
- electrically conductive wall: electrical and surface resistance $<10^3 \Omega$ (according to NFPA 652 $<10^6 \Omega$)
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: pneumatic transport of flammable dusts and bulk materials (Zone 20, 21, 22 inside)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- up to 400 °C

Design

- Metal hose
- profiled metal strip, galvanised steel
- hooked profile
- seal: glass fibre

Delivery variants

- further diameters available on request
- without sealing or with rubber sealing

| I.D. | outer Ø | Bending Radius | Weight | Dimensions in Stock | Production Lengths | Order No. |
|--------------|---------|----------------|--------|---------------------|--------------------|---------------|
| (in / mm) | (mm) | (mm) | (kg/m) | (m) | (m) | |
| - / 20 | 24.00 | 90.00 | 0.35 | 10 | - | 375-0020-2880 |
| 1 / 25 | 29.00 | 98.00 | 0.43 | 10 | - | 375-0025-2880 |
| - / 30 | 34.00 | 115.00 | 0.51 | 10 | - | 375-0030-2880 |
| 1,25 / 32 | 36.00 | 124.00 | 0.55 | 10 | - | 375-0032-2880 |
| 1,36 / 35 | 39.00 | 133.00 | 0.59 | 10 | - | 375-0035-2880 |
| 1,5 / 38 | 42.00 | 136.00 | 0.65 | 10 | - | 375-0038-2880 |
| - / 40 | 45.00 | 135.00 | 0.68 | 10 | - | 375-0040-2880 |
| 1,75 / 44-45 | 50.00 | 143.00 | 0.76 | 10 | - | 375-0045-2880 |
| 2 / 50-51 | 55.00 | 155.00 | 0.84 | 10 | - | 375-0050-2880 |
| - / 55 | 60.00 | 173.00 | 0.90 | 10 | - | 375-0055-2880 |
| 2,36 / 60 | 66.00 | 185.00 | 1.01 | 10 | - | 375-0060-2880 |
| 2,5 / 63-65 | 71.00 | 198.00 | 1.09 | 10 | - | 375-0065-2880 |
| - / 70 | 76.00 | 205.00 | 1.17 | 10 | - | 375-0070-2880 |
| 3 / 75-76 | 81.00 | 218.00 | 1.25 | 10 | - | 375-0075-2880 |
| - / 80 | 86.00 | 230.00 | 1.34 | 10 | - | 375-0080-2880 |
| 3,5 / 89-90 | 97.00 | 235.00 | 1.85 | 10 | - | 375-0090-2880 |
| 4 / 100-102 | 107.00 | 250.00 | 2.04 | 10 | - | 375-0100-2880 |
| - / 110 | 117.00 | 275.00 | 2.24 | 10 | - | 375-0110-2880 |
| 4,72 / 120 | 127.00 | 320.00 | 2.44 | 10 | - | 375-0120-2880 |
| 5 / 125-127 | 132.00 | 338.00 | 2.54 | 10 | - | 375-0125-2880 |
| - / 130 | 139.00 | 345.00 | 2.93 | 10 | - | 375-0130-2880 |
| 5,5 / 140 | 149.00 | 360.00 | 3.13 | 10 | - | 375-0140-2880 |
| 6 / 150-152 | 159.00 | 385.00 | 3.35 | 10 | - | 375-0150-2880 |
| 6,3 / 160 | 169.00 | 410.00 | 3.57 | 10 | - | 375-0160-2880 |


Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.

METAL HOSE 375 HT



| I.D. | outer Ø | Bending Radius | Weight | Dimensions in Stock | Production Lengths | Order No. |
|-------------|---------|----------------|--------|---------------------|--------------------|---------------|
| (in / mm) | (mm) | (mm) | (kg/m) | (m) | (m) | |
| - / 170 | 179.00 | 435.00 | 3.72 | - | 10 | 375-0170-2880 |
| 7 / 178-180 | 189.00 | 455.00 | 4.01 | 10 | - | 375-0180-2880 |
| 8 / 200-203 | 211.00 | 460.00 | 5.51 | 5 10 | - | 375-0200-2880 |
| - / 225 | 236.00 | 518.00 | 6.18 | 5 10 | - | 375-0225-2880 |
| - / 250 | 261.00 | 575.00 | 6.85 | 5 | - | 375-0250-2880 |
| - / 275 | 286.00 | 633.00 | 7.52 | 5 | - | 375-0275-2880 |
| - / 300 | 311.00 | 700.00 | 8.20 | 5 | - | 375-0300-2880 |

Accessories



CONNECT 203-204




CONNECT 206



CONNECT 202



CONNECT 270-271



CONNECT 205

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.