



Aluminium air conditioning hose, flame retardant (M0), self-locking

Applications

- flexible hose/ ducting for gases
- Air conditioning in marine applications
- Kitchen hood, fume hood, exhaust air duct

Properties

- highly flexible + compressible 3:1
- retaining any adjusted position
- conforms to RoHS guideline

Temperature Range

- 300°C

Design

- Metal hose
- Pressure max. 300 mm H2O

Delivery variants

- silver
- further diameters and lengths available on request

I.D.	outer Ø	Bending Radius	Weight	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	
3 / 75-76	85.00	38.00	0.00	3	377-0075-1000
- / 80	90.00	40.00	0.00	3	377-0080-1000
3,5 / 89-90	100.00	45.00	0.00	3	377-0090-1000
4 / 100-102	110.00	50.00	0.00	3	377-0100-1000
- / 110	120.00	55.00	0.00	3	377-0110-1000
4,72 / 120	130.00	60.00	0.00	3	377-0120-1000
5 / 125-127	135.00	63.00	0.00	3	377-0125-1000
5,5 / 140	150.00	70.00	0.00	3	377-0140-1000
6 / 150-152	160.00	75.00	0.00	3	377-0150-1000
6,3 / 160	170.00	80.00	0.00	3	377-0160-1000
7 / 178-180	190.00	90.00	0.00	3	377-0180-1000
8 / 200-203	210.00	100.00	0.00	3	377-0200-1000
- / 250	260.00	125.00	0.00	3	377-0250-1000
11 / 280	290.00	140.00	0.00	3	377-0280-1000
- / 300	310.00	150.00	0.00	3	377-0300-1000
- / 315	325.00	158.00	0.00	3	377-0315-1000
- / 350	360.00	175.00	0.00	3	377-0350-1000
- / 400	410.00	200.00	0.00	3	377-0400-1000

Accessories



CONNECT 270-271



CLAMP 208

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.