



PVC hose, heavy

Applications

- flexible hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- airport, airplane, rail vehicle, train, railway, boat, ship/ vessel, yacht: toilet discharging/ disposal
- agricultural industry: irrigation, fertilizers, insecticides
- caravan/ trailer, mobile home/ camper/ RV, boat, ship/ vessel, yachts: sanitary installation, water supply

Properties

- heavy duty
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH
- In compliance with Regulation (EU) No. 10/2011 for simulants A, B, C

Temperature Range

- -10°C to 60°C

Design

- Full plastic hose

- hard plastic spiral integrated in wall
- spiral: rigid PVC
- smooth interior
- wall: soft PVC

Delivery variants

- further diameters and lengths available on request
- green-transparent (standard)
- special colours: coloured spiral, full coloured
- customer-specific branding

I.D.	outer Ø	Vacuum	Operating pressure (20°C)	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
1 / 25	30.60	0,589	6,000	130.00	0.25	50	25	380-0025-8000
3 / 75-76	85.00	0,491	4,000	530.00	1.15	50	-	380-0076-8000

Accessories



CLAMP 208



CLAMP 211