



PVC hose, heavy duty

Applications

- flexible hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- airport, airplane, rail vehicle, train, railway, boat, ship/ vessel, yacht: lavatory waste
- agricultural industry: irrigation, fertilizers, insecticides
- caravan/ trailer, mobile home/ camper/ RV, boat, ship/ vessel, yachts: sanitary installation, water supply

Properties

- heavy duty
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH
- In compliance with Regulation (EU) No. 10/2011 for simulants A, B, C

Temperature range

- 14°F to 140°F

Design

- Full plastic hose

- hard plastic spiral integrated in wall
- spiral: rigid PVC
- smooth interior
- wall: soft PVC

Delivery variants

- further diameters and lengths available on request
- green-transparent (standard)
- special colors: colored spiral, full colored
- customer-specific branding

| I.D. | outer Ø | Vacuum | Operating pressure (68°F) | Bending radius | Weight | Dimensions in Stock | Production lengths | Order No. |
|-----------|---------|--------|---------------------------|----------------|---------|---------------------|--------------------|---------------|
| (in / mm) | (in) | (inHG) | (bar) | (in) | (lb/ft) | (ft) | (ft) | |
| 1 / 25 | 1.205 | 17.393 | 6,000 | 5.118 | 0.168 | 100 | 50 | 380-0025-8000 |
| 3 / 75-76 | 3.346 | 14.499 | 4,000 | 20.866 | 0.773 | 100 | - | 380-0076-8000 |

Accessories



CLAMP 208



CLAMP 211