



PVC hose, heavy duty

Applications

- flexible hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- airport, airplane, rail vehicle, train, railway, boat, ship/ vessel, yacht: lavatory waste
- agricultural industry: irrigation, fertilizers, insecticides
- caravan/ trailer, mobile home/ camper/ RV, boat, ship/ vessel, yachts: sanitary installation, water supply

Properties

- heavy duty
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH
- In compliance with Regulation (EU) No. 10/2011 for simulants A, B, C

Temperature range

- 14°F to 140°F

Design

- Full plastic hose

- hard plastic spiral integrated in wall
- spiral: rigid PVC
- smooth interior
- wall: soft PVC

Delivery variants

- further diameters and lengths available on request
- green-transparent (standard)
- special colors: colored spiral, full colored
- customer-specific branding

I.D.	outer Ø	Vacuum	Operating pressure (68°F)	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(inHG)	(bar)	(in)	(lb/ft)	(ft)	(ft)	
1 / 25	1.205	17.393	6,000	5.118	0.168	100	50	380-0025-8000
3 / 75-76	3.346	14.499	4,000	20.866	0.773	100	-	380-0076-8000

Accessories



CLAMP 211



CLAMP 208