



## Clamp profile hose (clip hose), (up to +170°C)

### Applications

- flexible hose/ ducting for hot and cold gases and for dust, powder, fibres
- chemical industry: chemical vapours, vapour return hose at loading arm, paint steam, spray mist extraction
- industrial washing machine: air blower hose for drying
- high temperature extraction: oven, foundry, furnace, smelting, ceramics industry, glass industry, steel plant, aluminium mill
- bellows, compensators

### Properties

- abrasion protection via external clamp profile

- secure clamping of the wall within the clamp profile
- highly flexible + compressible 4:1
- vibration resistant
- very good heat resistance
- good resistance to oil, gasoline and chemicals
- good resistance to alkalis and acids
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- 40°C to 170°C

### Design

- CP construction
- clamp profile supporting spiral: galvanised steel
- wall: CSM coated polyester fabric

### Delivery variants

- further diameters and lengths available on request
- stainless steel (INOX) clamp profile
- double-layer

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	
1,5 / 38	50.00	0,785	0,450	21.00	0.57	6	450-0038-0000
- / 40	52.00	0,765	0,440	22.00	0.59	6	450-0040-0000
2 / 50-51	62.00	0,630	0,380	25.00	0.76	6	450-0050-0000
- / 55	67.00	0,600	0,350	27.00	0.82	6	450-0055-0000
2,36 / 60	72.00	0,570	0,320	28.00	0.89	6	450-0060-0000
2,5 / 63-65	77.00	0,545	0,290	30.00	0.96	6	450-0065-0000
- / 70	82.00	0,525	0,260	31.00	1.03	6	450-0070-0000
3 / 75-76	87.00	0,500	0,230	33.00	1.10	6	450-0075-0000
- / 80	92.00	0,485	0,200	34.00	1.16	6	450-0080-0000
3,5 / 89-90	102.00	0,450	0,140	37.00	1.30	6	450-0090-0000
4 / 100-102	112.00	0,300	0,120	28.00	1.03	6	450-0100-0000
- / 110	122.00	0,285	0,105	30.00	1.13	3 6	450-0110-0000
4,5 / 114-115	127.00	0,275	0,098	32.00	1.17	3 6	450-0115-0000
4,72 / 120	132.00	0,270	0,090	32.00	1.22	3 6	450-0120-0000
5 / 125-127	137.00	0,260	0,085	34.00	1.27	3 6	450-0125-0000
- / 130	142.00	0,255	0,075	34.00	1.32	3 6	450-0130-0000
5,5 / 140	152.00	0,245	0,060	36.00	1.42	3 6	450-0140-0000
6 / 150-152	162.00	0,165	0,050	38.00	1.04	3 6	450-0150-0000
6,3 / 160	172.00	0,160	0,045	40.00	1.11	3 6	450-0160-0000
6,5 / 165	177.00	0,155	0,040	41.00	1.14	3 6	450-0165-0000
- / 170	182.00	0,155	0,040	42.00	1.17	3 6	450-0170-0000
- / 175	187.00	0,150	0,040	44.00	1.21	3 6	450-0175-0000
7 / 178-180	192.00	0,150	0,040	44.00	1.24	3 6	450-0180-0000
8 / 200-203	212.00	0,140	0,030	48.00	1.37	3 6	450-0200-0000
- / 215	227.00	0,135	0,030	52.00	1.47	3 6	450-0215-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	
- / 225	237.00	0,130	0,025	54.00	1.54	<b>3 6</b>	450-0225-0000
9 / 228-229	240.00	0,130	0,025	57.00	1.56	<b>3 6</b>	450-0228-0000
- / 250	262.00	0,100	0,025	58.00	1.71	<b>3 6</b>	450-0250-0000
10 / 254	266.00	0,095	0,025	60.00	1.85	<b>3 6</b>	450-0254-0000
- / 275	287.00	0,090	0,020	64.00	1.87	<b>3 6</b>	450-0275-0000
11 / 280	292.00	0,090	0,020	65.00	1.96	<b>3 6</b>	450-0280-0000
- / 300	312.00	0,085	0,015	68.00	2.04	<b>3 6</b>	450-0300-0000
12 / 305	317.00	0,085	0,015	69.00	2.07	<b>3 6</b>	450-0305-0000
- / 315	327.00	0,085	0,015	71.00	2.14	<b>3 6</b>	450-0315-0000
- / 325	337.00	0,080	0,015	74.00	2.21	<b>3 6</b>	450-0325-0000
13 / 330	342.00	0,080	0,015	75.00	2.25	<b>3 6</b>	450-0330-0000
- / 350	362.00	0,065	0,015	78.00	2.37	<b>3 6</b>	450-0350-0000
- / 400	412.00	0,060	0,010	88.00	2.71	<b>3 6</b>	450-0400-0000
16 / 405-406	418.00	0,055	0,010	90.00	2.75	<b>3 6</b>	450-0406-0000
- / 450	462.00	0,055	0,010	98.00	3.04	<b>3 6</b>	450-0450-0000
18 / 457	469.00	0,050	0,010	100.00	3.09	<b>3 6</b>	450-0457-0000
- / 500	512.00	0,050	0,005	108.00	3.37	<b>3 6</b>	450-0500-0000
20 / 508	520.00	0,035	0,005	110.00	3.41	<b>3 6</b>	450-0508-0000
- / 600	612.00	0,030	0,005	128.00	4.04	<b>3</b>	450-0600-0000
24 / 610	622.00	0,030	0,005	130.00	4.12	<b>3</b>	450-0610-0000
- / 700	712.00	0,025	0,002	148.00	4.71	<b>3</b>	450-0700-0000
- / 900	912.00	0,020	0,001	188.00	6.04	<b>3</b>	450-0900-0000
- / 1000	1012.00	0,020	0,001	208.00	6.71	<b>3</b>	450-1000-0000

## Accessories



CLAMP 212



CONNECT 270-271



CONNECT 228



CLAMP 217



CLAMP 213

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).