

Membrane diffuser tube

Applications

- membrane tube diffuser, for industrial and municipal wastewater treatment plant, pressure diffusion with fine bubbles, oxygen input for nitrification in activation basins, permanent and intermittent ventilation
- oxygen input and circulation in xed-bed and bioreactors, thorough mixing of activation basins, sand trap louvre ventilation, renaturation of lakes and rivers, aquacultures, sh farming

Properties

- high energy savings when compared with comparative, market standard EPDM and silicone diffusers due to the much lower pressure loss
- extremely long lifetime and no curing due to the membrane not including a plasticizer
- very wide operating range: normal operation: 3-8, minimum 1, maximum 15 and purging operation 18 Nm³/(h*m_{aer.})
- comparatively high oxygen input and oxygen oxygen transfer efficiency even with low density systems

- very fine and uniform bubble formation due to an optimized perforation
- easily and quickly fitted
- very good resistance to waste water and municipal sewerage in accordance with the latest instructions DWA-M 115
- extremely tear-resistant and abrasion-resistant (mechanical strength around 2.5-4 times that of most of the EPDM and silicone materials)
- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- conforms to RoHS guideline

Temperature range

- -40 °F to 195 °F

Design

- wall: special premium ether-polyurethane (Pre-PUR®)
- wall thickness 0.02 in approx.

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colors: full colored
- customer-specific branding

| Size | I.D. | Length | Ventilation length | Weight | Order No. |
|-------|-----------|--------|--------------------|----------|---------------|
| (in) | (in / mm) | (in) | (in) | (lb/pcs) | |
| 2.480 | 64,5 | 22.441 | 19.685 | 0.221 | 630-0570-2702 |
| 2.480 | 64,5 | 32.283 | 29.528 | 0.331 | 630-0820-2702 |
| 2.480 | 64,5 | 42.126 | 39.370 | 0.441 | 630-1070-2702 |


Accessories



CONNECT 684



CLAMP 682



CONNECT 683



CONNECT 685



CONNECT 229

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.